



# Stratasys F900

## **Designed and built for size, throughput, precision and repeatability.**

The Stratasys F900™ 3D Printer is the most precise and powerful FDM system available. With the largest build size of any Fortus® system, the Stratasys F900 is designed to handle the most demanding manufacturing needs. The accuracy, repeatability and predictability are unmatched, and the control software leverages the system's hardware to deliver superior throughput and reliability.

The Stratasys F900 uses engineering-grade thermoplastics to build robust production parts, jigs, fixtures, factory tooling and functional prototypes. Large parts are printed fast with the standard, large T40A tip to help meet production demands with ease.

The Stratasys F900 offers a streamlined workflow and easier job monitoring with an internal camera, GrabCAD Print™ software and MTConnect readiness. Standard certifications are included and reduce workload to qualify 3D printers for a production floor.



LEARN MORE ABOUT THE STRATASYS F900 AT [STRATASYS.COM](https://www.stratasys.com)

**stratasys**

THE 3D PRINTING SOLUTIONS COMPANY



# Stratasys F900

## System Specifications

### SYSTEM CONFIGURATION

|                             |   |
|-----------------------------|---|
| <b>Build Envelope (XYZ)</b> | 914.4 x 609.6 x 914.4 mm (36 x 24 x 36 in.) Platen supports two build zones for either a small or large build sheet   |
| <b>Material Delivery</b>    | Two build material canisters 1508 cc (92 in. <sup>3</sup> ), Two support material canisters 1508 cc (92 in. <sup>3</sup> ), Auto changeover between canisters |

### MATERIAL OPTIONS

| Layer Thickness:          | ASA   | ABS-M30™  | ABS-M30i™   | ABS-ESD7™   | PC-ABS  | PC-ISO™  | PC  | ULTEM™ 9085 resin  | ULTEM 1010 resin  | PPSF  | FDM Nylon 12™   | FDM Nylon 6™  | ST-130™   | FDM Nylon 12CF™   |
|---------------------------|---|---|---|---|---|--|---|--|---|---|---|---|---|---|
| 0.020 inch (0.508 mm)     | X   |   |   |   |   |  |   |  | X   |   |   |   |   |   |
| 0.013 inch (0.330 mm)     | X   | X   | X   |   | X   | X  | X   | X  | X   |   | X   | X   | X   |   |
| 0.010 inch (0.254 mm)     | X   | X   | X   | X   | X   | X  | X   | X  | X   | X   | X   | X   |   | X   |
| 0.007 inch (0.178 mm)     | X   | X   | X   | X   | X   | X  | X   |  |   |   | X   |   |   |   |
| 0.005 inch (0.127 mm)     | X   |   |   |   |   |  |   |  |   |   |   |   |   |   |
| <b>Support Structure:</b> | Soluble   | Soluble   | Soluble   | Soluble   | Soluble   | Breakaway  | Breakaway, Soluble  | Breakaway  | Breakaway   | Breakaway   | Soluble   | Soluble   | Breakaway   | Soluble   |
| <b>Available Colors:</b>  | <ul style="list-style-type: none"> <li>■ Black</li> <li>■ Dark Gray</li> <li>■ Light Gray</li> <li>□ White</li> <li>■ Ivory</li> <li>■ Dark Blue</li> <li>■ Green</li> <li>■ Yellow</li> <li>■ Orange</li> <li>■ Red</li> </ul> | <ul style="list-style-type: none"> <li>■ Ivory</li> <li>□ White</li> <li>■ Black</li> <li>■ Red</li> <li>■ Blue</li> <li>■ Dark Grey</li> </ul> | <ul style="list-style-type: none"> <li>■ Ivory</li> </ul> | <ul style="list-style-type: none"> <li>■ Black</li> </ul> | <ul style="list-style-type: none"> <li>■ Black</li> </ul> | <ul style="list-style-type: none"> <li>■ Translucent Natural</li> <li>□ White</li> </ul> | <ul style="list-style-type: none"> <li>■ White</li> </ul> | <ul style="list-style-type: none"> <li>■ Tan</li> <li>■ Black</li> </ul> | <ul style="list-style-type: none"> <li>■ Natural</li> </ul> | <ul style="list-style-type: none"> <li>■ Tan</li> </ul> | <ul style="list-style-type: none"> <li>■ Black</li> </ul> | <ul style="list-style-type: none"> <li>■ Black</li> </ul> | <ul style="list-style-type: none"> <li>■ Natural</li> </ul> | <ul style="list-style-type: none"> <li>■ Black</li> </ul> |

### OTHER SPECIFICATIONS

|  |   |
|--|---|
| <b>System Size and Weight</b>              | 2772 x 1683 x 2027 mm (109.1 x 66.3 x 78.1 in.); 2869 kg (6325 lbs.). With Manufacturing Light Tower: 2772 x 1683 x 2281 mm (109.1 x 66.3 x 89.8 in.)   |
| <b>Achievable Accuracy</b>                 | Parts are produced within an accuracy of +/- .0035 in. or +/- .0015 in. per in., whichever is greater (+/- .089 mm or +/- .0015 mm per mm whichever is greater). Z part accuracy includes an additional tolerance of +/- the selected slice height. <i>Note: Accuracy is geometry dependent. Achievable accuracy specification derived from statistical data at 95% dimensional yield. See Fortus 900mc™ Accuracy Study white paper for more information.</i> |
| <b>Network Communication</b>               | 10/100 base T connection. Ethernet protocol.  |
| <b>Operator Attendance</b>                 | Limited attendance for job start and stop required.   |
| <b>Operating Environment<sup>1</sup></b>   | Maximum room temperature of 85°F (29°C). Maximum room humidity of 80%.  |
| <b>Power Requirements<sup>1</sup></b>      | 230 VAC (three phase) 50/60Hz, Voltage fluctuation +/- Current 40A  |
| <b>Additional Requirements<sup>1</sup></b> | Compressed Air Required 90-120 psi with a minimum flow of 20 SCFM   |
| <b>Regulatory Compliance<sup>1</sup></b>   | CE, NRTL Listed   |
| <b>Software</b>                            | All Fortus systems include Insight™ and Control Center™ job processing and management software. Compatible with GrabCAD Print for use with job reports, scheduling and remote monitoring.   |
| <b>Operating System</b>                    | Microsoft Windows 8.1 and Windows 8 (Pro, Enterprise), Microsoft Windows 7 (Pro, Enterprise, Ultimate), Microsoft Windows Vista (Business, Enterprise, Ultimate), Microsoft Windows Server 2008, Microsoft Windows Server 2003  |

<sup>1</sup>See Stratasys F900 Site Prep Guide for detailed power and environmental specs



PADT  
480.813.4884  
www.padtinc.com

STRATASYS.COM  
ISO 9001:2008 Certified

© 2015, 2016, 2018 Stratasys. All rights reserved. Stratasys, FDM, Fortus and Finishing Touch are registered trademarks of Stratasys Inc. Stratasys F900, Fortus 900mc, GrabCAD Print, Insight, FDM Technology, Smart Supports, XTEND, SR-30, SR-35, SR-100, SR-110, ABSplus, ABSi, ABS-M30, ABS-M30i, ABS-ESD7, PC-ISO, FDM Nylon 12, FDM Nylon 12CF, ST-130 and TouchWorks are trademarks of Stratasys, Inc. ULTEM is a registered trademark of SABIC or affiliates. All other trademarks are the property of their respective owners, and Stratasys assumes no responsibility with regard to the selection, performance, or use of these non-Stratasys products. Product specifications subject to change without notice. PSS\_FDM\_StratasysF900\_A4\_0518a